

Factory Add: Taiwanese Investment Park, Quanzhou, Fujian Province, China. Web Site: www.socmachinery.com

IC Forklift HNF280

Model	HNF280				Unit	
Performance	Load capacity				kg	28000
	Load center				mm	1250
	Maximum fork height (h4)				mm	3500
	Lifting speed(wz/wo load)				mm/s	260/280
	Mast tilt angle (forward/backward)				o	6/12
	Max. Travel speed (full load/without load)				kmh	24/28
	Turning radius(outside)				mm	7260
	Grade ability (wz/wo load)				%	20/21
Dimension	Overall length (wz/wo fork)				mm	9590/7150
	Fork size (L*W*T)				mm	2440*300*110
	Overall width				mm	3200
	Width of fork carriage				mm	3100
	O-11 1	: . 1.4		mast lowed	mm	3950
	Overall h	ieignt		overhead guard	mm	3800
	Wheelbase				mm	4800
	Ground clearance (wz load) wheelbase center mast lowered point			eelbase center	mm	410
				st lowered point	mm	350
Weight	Total weight				kg	39000
Tire	numbers & size Front					4*14.00-24/32PR
	numbers & size Rear					2*14.00-24/32PR
	Wheel tread		Front		mm	2200
			Rear		mm	2390
Brake	Service Air over Hydraulic clamp			ver Hydraulic clan	np disc brake	
	Parking Spring press clamp disc b			g press clamp disc	brake	
Transmission	Manufact	urer /Type	ZHONGNAN/ Automatic power-shift			
	Number of speed Forward2/Reverse1			ard2/Reverse1		
Engine Diesel	Option	Manufacturer/N		lodel	WEICHAI	WP10G220E341
	1.	Rated power/rotate speed			kw/r.pm	162/2000
	Option	Manufac	turer/Model		CUMMINS	QSB8.3-C260
	2. Rated power/rotate speed			ate speed	kw/r.pm	194/2200
Optional attachment	Per request of customer					



Features:

- 1. Compact body structure, Optimized mast design, with wide view: Optimized mast with small clearance, compact structure, which provide wide front view for the operator. It is good for safe-working improvement and the increasing of the work efficiency.
- 2. Well organized engine water plus air cooling system maintain temperature stable at around 90°C transmission oil temperature below 40°C, thus prolong lifespan of oil seal ,reduce risk of oil-leakage, water-leakage or moving part wearing in engine, transmission box.
- 3. Low maintenance cost that benefit ROI

