

Add: Taiwanese Investment Park, Quanzhou, Fujian Province, China. **Web Site:** www.socmachinery.com

TEL: +86-592-5650662

Fax: +86-592-5650876

E-mail: alex@socmachinery.com.cn

Specification

Model	HNF320		Unit		
Performance	Load capacity		kg	32000	
	Load center		mm	1250	
	Maximum fork height		mm	3500	
	Lifting speed(wz/wo load)		mm/s	260/280	
	Mast tilt angle (forward/backward)		°	6/12	
	Max. Travel speed (full load/without load)		kmh	24/28	
	Turning radius(outside)		mm	7260	
	Grade ability (wz/wo load)		%	20/21	
Dimension	Overall length (wz/wo fork) (l1		mm	9590/7150	
	Fork size (L*W*T)		mm	2440*320*110	
	Overall width		mm	3200	
	Width of fork carriage		mm	3100	
	Overall height	mast lowed		mm	4010
		overhead guard		mm	3950
	Wheelbase		mm	4800	
	Ground clearance (wz load)	wheelbase center		mm	460
mast lowered point		mm	400		
Weight	Total weight		kg	41000	
Tire	Tire numbers & size Front			4*14.00-24/32PR	
	Tire numbers & size Rear			2*14.00-25/32PR	
	Wheel tread	Front		mm	2420
		Rear		mm	2390
Brake	Service	Air over Hydraulic clamp disc brake			
	Parking	Spring press clamp disc brake			
Transmission	Manufacturer /Type	SOCMA / Automatic power-shift			
	Number of speed	Forward2/Reverse1			
Engine Diesel	Option 1.	Manufacturer/Model	WEICHAI	WP10G240E341	
		Rated power/rotate speed	kw/r.pm	178/2200	
	Option 2.	Manufacturer/Model	CUMMINS	QSB8.3-C260	
		Rated power/rotate speed	kw/r.pm	194/2200	
Top lifting Spreader	Suit for 40 feet container lifting, mounting on fork, hydraulic control, removable				





